

Research and development works | Accredited Group of Laboratories | Notified Body N° 1488 | EOTA member | Certified management systems ISO 9001, ISO 27001

REACTION TO FIRE CLASSIFICATION REPORT IN ACCORDANCE WITH PN-EN 13501-1+A1:2010

Contract no. 02039/18/Z00NZP

Sponsor:	Steico Sp. z o.o. ul. Przemysłowa 2 64-700 Czarnków			
Prepared by:	Building Research Institute; 1, Filtrowa str. 00-611 Warszawa, Poland			
Product name:	Wood wool with trade name Steico Zell			
Classification report No.:	02039.1/18/Z00NZP-ENG			
Issue number:	1 (version in English of report no. 01398.1/18/Z00NZP) Copy no.1			
Date of issue:	28.06.2018			

This classification report consists of three pages and may only be used or reproduced in its entirety.

1. Introduction

This classification report defines the classification assigned to wood wool with trade name Steico Zell in accordance with the procedures given in PN-EN 13501-1+A1:2010.

2. Details of classified product

2.1 General

The product is defined as wood wool with trade name Steico Zell used for thermal insulations in construction.

2.2 Product description

The product, is described below.

Product description:

Density of wood wool with trade name Steico Zell: from 32 kg/m³ to 40 kg/m³ ± 15%.

Wood wool with trade name Steico Zell is produced in manufacturing site Steico Sp. z o.o. ul. Przemysłowa 2 64-700 Czarnków.

3. Test reports & test results in support of classification

3.1 Test reports

Name of laboratory	Name of sponsor	Test report no.	Test method
Fire Testing Laboratory of ITB	Steico Sp. z o.o.	LZP05-01398/18/Z00NZP	DN EN ICO 44005 0.0040
		LZP06-01398/18/Z00NZP	PN-EN ISO 11925-2:2010
		LZP01-01398/18/Z00NZP	PN-EN 13823+A1:2014
		LZP02-01398/18/Z00NZP	PN-EN 13623+A1.2014

3.2 Test results

2 lest results			Results	
Test method	Parameter	Number of tests	Continuous parameter – mean (m)	Compliance with parameters
PN-EN ISO 11925-2 +AC:2011	F _s ≤150 mm		(-)	Υ
Surface and edge exposure exposure time 30 s	Flaming 6 Droplets/particles		(-)	N
PN-EN ISO 11925-2+AC:2011	F _s ≤150 mm		(-)	Υ
Surface and edge exposure exposure time 30 s	Flaming Droplets/particles	6	(-)	N
PN-EN 13823+A1:2014	$FIGRA_{0,2MJ}$ $FIGRA_{0,4MJ}$ $LFS < edge$ $THR_{600s}[MJ]$ $SMOGRA[m^2/s^2]$ $TSP_{600s}[m^2]$ $Flaming$ $Droplets/particles$	3	72,1 67,1 (-) 6,7 11,8 170,7 (-)	(-) (-) Y (-) (-) (-) N
PN-EN 13823+A1:2014	FIGRA _{0,2MJ} FIGRA _{0,4MJ} LFS < edge THR _{600s} [MJ] SMOGRA [m ² /s ²] TSP _{600s} [m ²] Flaming Droplets/particles		66,7 60,5 (-) 6,1 10,2 152,5 (-)	

(–): do not concern Y: Yes

N: No

4 Classification and field of application

4.1 Reference of classification

This classification has been carried out in accordance with PN-EN 13501-1+A1:2010.

4.2 Classification

The product, wood wool with trade name Steico Zell described in point 2 this classification report, in relation to its reaction to fire behaviour are classified:

B

The additional classification in relation to smoke production is:

s2

The additional classification in relation to flaming droplets/particles is:

d0

The format of the reaction to fire classification for construction products excluding floorings and linear pipe thermal insulation products is:

Fire behaviour		Smoke production			Flaming droplets		
В	-	S	2	9	d	0	

i.e.: B-s2,d0

Reaction to fire classification: B-s2,d0

4.3 Field of application

This classification is valid for the following product parameters:

Wood wool with trade name Steico zell described in point 2 this classification report.

This classification is valid for the following substrates, fixing and air gaps:

- Substrates with minimum reaction to fire class A2-s3,d0 and gypsum plaster boards.

5 Limitations

This classification given remains valid as long as:

- test method remains unchanged,
- product standard or technical approval remains unchanged,
- constructional or material modifications do not exceed limits of the field of application defined in 4.3.

This classification document does not represent type approval or certification of the product.

SIGNED

APPROVED

Andrzej Kolbrecki Ph.D. Eng.

ACTING HEAD of Fire Research Departament

Bartlomiej Papis, PhD Eng.